

# INFINITY II PRO-GLINK

# Specification Sheet

**DESCRIPTION:** ProLink is an optional crosslinker for the final coat of Infinity II. In addition to speeding up full cure times, ProLink increases the already exceptional chemical resistance and anti-abrasion qualities of the Infinity II topcoat.

**PREPARATION:** ProLink does not require any special surface preparation other than that already done for standard finish jobs. Maintain product integrity by keeping bottle tightly capped and storing in a cool, dry place before use.

For best results, use ProLink as an additive in the final Infinity II coat over two seal coats of Infinity II or over a seal coat of Quality Seal and Infinity II. *Using ProLink in the seal coat or second coat is NOT recommended, as discoloration may occur.*

**APPLICATION:** ProLink should be stored and mixed at the same relative temperature as the Infinity II product into which it is being added. ProLink will not affect coverage rate or dry time.

**1** Mix equal parts water with ProLink crosslinker.  
*One 4 oz. bottle of ProLink crosslinks one gallon of Infinity II finish.*



**2** Shake ProLink contents thoroughly.



**3** Shake Infinity II for 15 seconds as you normally would.



**4** Slowly add ProLink mixture.



**5** Shake combined contents aggressively for 30 seconds.



**6** Allow crosslinked Infinity II finish to set for 10 minutes before use.



**7** Apply crosslinked finish mixture during the final coat in accordance to Infinity II label directions.



*Once ProLink is added to Infinity II, mixture must be used within six hours and cannot be re-crosslinked.*

**STORAGE:** Store in a cool, dry place.  
DO NOT FREEZE.

**SHELF LIFE:** One year in unopened container.

**POT LIFE:** 6-8 hours

**DISPOSAL:** Dispose of unused material in accordance with local, state and federal regulations.

Before using ProLink crosslinker, READ ALL INSTRUCTIONS AND CAUTION STATEMENTS on ProLink label and Infinity II label. Any mixture containing crosslinker will include hazards from all components. Wear safety glasses, protective gloves and an appropriate, properly fitted NIOSH approved respirator while using this product. OBSERVE ALL APPLICABLE PRECAUTIONS.

**For Professional Use Only.**



Read Material Safety Data Sheet and Label Precautions before using this product.  
**GLITSA AMERICAN, INC. • SEATTLE, WA 98108 • 1-800-527-8111**  
**VISIT OUR WEBSITE AT WWW.GLITSA.COM**